Site Name: Well Hall Sports Ground, Kidbrooke Lane, Eltham Area (ha): 6.96 **Current Use:** Sports Playing pitch Proposed Use: Residential, Retail and Vulnerability More Vulnerable Classification: playing pitch Fluvial Source: Flood Zone 1 Flood Zone 2 Flood Zone 3 Flood Zone 3b Area Benefiting from Defences: (<0.1% EP): (0.1% AEP): 0% (1% AEP): 0% (5%AEP): 0% 100% **Surface Water Source** Risk of Flooding from Surface Water (RoFSW) Hiah - Flood Defences Risk of Flooding from Surface Water © Crown Copyright and database rights 2018. 600 1.000 m 200 400 800 Published using the Open Government License (OGL) version 3.0 Figure A Risk of Flooding from Surface Water (RoFSW) **Critical Drainage Area** Group6_013 (0% Overlap) **Groundwater Source** N/A **Bedrock Geology** London Clay Formation **Superficial Geology Bedrock Aquifer** Unproductive (100% Overlap) Superficial Aquifer N/A Designation Designation **Potential Groundwater Flooding Zone** N/A Other Sources Internal Flood Incidents: NoData External Flood Incidents: NoData Sewer Flooding (within 4 digit postcode) **Artificial sources**

Site Specific Recommendations

The site is currently used as a sports playing pitch. The site is within Flood Zone 1 and surface water flood risk is high. An assessment of surface water flow paths should be made prior to site design, to encourage the location of buildings and more vulnerable aspects of the development away from those areas at risk of surface water ponding and surface water flow paths. This site is suitable for water compatible open space development.

Although the site is within Flood Zone 1, it is good practice to set finished floor levels a minimum of 300mm above ground level in order to reduce the risk of flooding from surface water, which is at high risk in this area. It is recommended that consideration is given to the flow of surface water during the development of the site masterplan and layout to ensure effective management of surface water flows. A number of flood resistance and resilience measures can be implemented into new developments to mitigate potential flooding. Guidance on resilience measures can be found in the document 'Improving the Flood Performance of New Buildings, Flood Resilient Construction' published by The Department for Communities and Local Government (CLG).

Surface water flow paths should be assessed to inform the strategic location of SuDS and techniques to route flows around the site. It is possible that the management of the flow will help to reduce surface water flow and ponding to the area outside the site Careful consideration should be given to the use of fences and landscaping walls so as to prevent causing obstruction to flow routes and increasing the risk of flooding to the site or neighbouring areas.

Reference to the SWMP Appendix D Figure D6 identifies that (prior to the completion of a site investigation to determine precise local conditions) infiltration of surface water into the ground is uncertain for the site. Site investigations will be required prior to the development of a Drainage Strategy for the site. Development should utilise sustainable urban drainage systems (SUDS) unless there

Site Name: Well Hall Sports Ground, Kidbrooke Lane, Eltham

are practical reasons for not doing so. The site is located within the Group6_013 Critical Drainage Area. The potential development must not increase flood risk to other areas within the CDA. Where an increased risk exists, developers need to provide a Drainage Strategy to demonstrate how they intend to address this, by what methods, over what timeframe and how maintenance of such works would be funded over its lifetime. This should include a consideration of SuDS in line with the London Plan 5.13 and Local Plan Policies. Surface water run-off should be managed in line with Royal Greenwich's surface water management requirements, as set out in Chapter 4 of the Developer Guidance.

Summary

The site is within Flood Zone 1 and in accordance with NPPF does not require the application of the Exception Test. However, the site is at High Risk of Surface Water Flooding. It is recommended that development is located away from the area at risk of flooding. If the site will increase the risk of flooding, a drainage strategy should be provided to show how the site will be drained. Where possible, SuDS should be used to drain the site. The proposed use of open space for the site would be suitable for water compatible use.